

FLEX-1[®]

TECHNICAL DATA

A-333 ACRYLIC LATEX SEALANT

Discription:

It is a one part, water based acrylic sealant that cures to a flexible and tough rubber with good adhesion to porous surface without primer. Suitable for sealing and filling gaps or joints where low demands of elongation are required.



Features:

1. Waterproof, Paintable.
2. Flexible
3. Excellent Adhesion to most construction materials

Properties:

Flex-1 A-333 ACRYLIC SEALANT	
System	Acrylic resin
Consistency	Pase
Hardness shore A	25-45
Tack free time	<1 Hr.
Working temperature	+ 5 °C to + 45 °C
Density	1.60
Ultimate elongation at break,%	>100
Excellent weatherproof ability	-40 °C. to 180 °C

Colors:

White and other colors base on customers' requirements

Where to use:

1. It is mainly for sealing the gaps or joints interior and exterior, such as doors and window frames, walls, window sills, prefab elements, stairs, skirting, corrugated roof sheets, chimneys, conduit-pipes and roof gutters.
2. It is also can be used on most construction materials, such as brick, concrete, plasterwork, asbestos cement, wood, glass, ceramic tiles, metals, aluminum, zinc and so on.
3. It is not suitable for permanently flexible sealing, for cars or spaces where wet conditions exist, e.g. aquaria, foundations and swimming pools