

## A-333 ACRYLIC LATEX SEALANT

---

### Application:

Surface treatment: The joint surfaces must be clean and free from dust, rust and grease. Tar and bitumen sub-strates reduce the bonding ability. In order to improve the bonding ability to strongly absorbing porous surfaces, such as stone, concrete, asbestos cement and plasterwork, these surfaces should first be primed with a diluted sealant (1 volume of Acrylic Sealant to 3-5 volumes of water) until the primer to dry completely

### Handling and safety:

Applicators are recommended to wear gloves and goggles when using FLEX-1 in case contact with eyes, flush immediately with clean water and seek medical assistance if symptoms persist.

### Cleaning:

Tools and equipment just can be clean with clean water immediately, after use hardener material can only be mechanically removed.

### Coverage:

Approximately linear 3 m. size 10 X 10 mm.

### Storage:

Acrylic Sealant is sensitive to frost and must be kept in tightly closed packing in a frost-proof place. The shelf life is about 2 years when stored in a cool, dry place. Opened tubes and cartridges should be stored as follows:

Tube: twist the nozzle applicator off the tube and screw the cap onto it.

Cartridge: twist off the plastic applicator-nozzle, cover the nozzle end of the cartridge with a plastic film and screw the applicator onto the cartridge again

### Cautions:

1. Do not apply at temperature below 0 °C.
2. Be not fit for continuous immersion in water.
3. Keep out of reach of children.