

Painting :

Painting is available 1 day to 1 days for water based paints after applying sealant. For immediately Painting should be available 4-6 hour after applying sealant.

Joint Dimensions :

Minimum Width : Should be 5 mm.
Maximum Width : not over 30 mm.
Minimum Depth : Should be 5 mm.
Recommendation : Joint depth should be half of the joint width

Health and Safety :

Do not swallow and avoid prolonged or repeated contact with skin. The uncured sealant may cause eyes and skin irritation. If contact with the eyes occur, wash eyes with copious quantities of water and consult a doctor if irritation persists. In case of skin contact wash affected areas with hand cleaner followed by soap and water. (More information see in MSDS)

PRODUCT :

FlexSil MS2 is a modified silicone sealant based on MS-Polymer. Flexsil-MS2 are suitable for a wide range of applications in construction and industry. These innovative, environmentally friendly, one-part, moisture curing MS Polymers are solvent. And isocyanate-free adhesives and sealant. They essentially combine the strength of Polyurethane with the weathering resistance of silicone and represent the latest generation on High-performance adhesive and sealant.

Distributor by :

Advantages :

- Excellent Durability & Weatherability applicable for most of joints due to the high performance.
- Non Staining Perfect Adhesion.
- Paintable, High UV Resistant.
- High Modulus with high Movement capability.
- Neutral curing type Stays elastic after curing.
- Good mechanical properties and easy to use.

Shelf life :

12 Months If stored in a cool and dry storage place at temperatures 25 C'

Colour : White , Gray

Packaging : 500 ml. and 600 ml.

Specification standard :

ASTM D412
ASTM C661
ASTM D2440

